

General information on Suunto PM-5 clinometer/ heightmeter range

Suunto PM-5

- Acrylic capsule
- Anodized light-alloy housing
- Optical adjustment for reading
- Parallax-free lens
- Jeweled bearing
- Damping liquid
- Nylon pouch with belt-loop
- Lanyard and metal lanyard ring
- Available also in feet scales for the US market
- 2-year warranty
- Dimensions: 75 x 52 x 15 mm
- Weight: 110 g

AVAILABLE VERSIONS

Clinometers

_PM-5/360 PC: Scales: $0 \pm 90^\circ$, $0 \pm 150\%$, conversion table: cosines $0-45^\circ$

_PM-5/360 S: Scales: $0 \pm 90^\circ$, secant, conversion table: cosines $0-45^\circ$

_PM-5/400 PC: Scales: 0 ± 100 gons, $0 \pm 150\%$, conversion table $0-50$ gons

_PM-5/6400: Scales: 0 ± 1600 mils, $0 \pm 150\%$

_PM-5/SPC: Scales: secant, $0 \pm 150\%$, conversion table: % - degrees

Combined Height and Clinometers

_PM-5/1520: Scales: 1:20 (0 ± 50 m), 1:15 (0 ± 35 m), conversion table: height in meters (1:20) into degrees

_PM-5/66: Scales: $0 \pm 90^\circ$, 1:66 (0 ± 200 ft), conversion table: % - degrees

_PM-5/1520 PC: Scales: 1:20 (0 ± 50 m), 1:15 (0 ± 35 m), $0 \pm 150\%$, conversion table: height in meters (1:20) into degrees

_PM-5/66 PC: Scales: $0 \pm 150\%$, 1:66 (0 ± 200 ft), conversion table: % - degrees

_PM-5/1520 D: 1:20 (0 ± 50 m), 1:15 (0 ± 35 m), $0 \pm 90^\circ$, conversion table: cosines $0 - 45^\circ$

